


MCBs and RCDs LR™ 6000

thermal magnetic MCBs from 6 A to 63 A - B and C curves
residual current devices from 25 A to 63 A - AC and A types



6048 96



6048 50



6021 93



6021 53

Dimensions (p. 183)

- MCBs: Conform to IEC 60898-1
- Breaking capacity: **6000** - IEC 60898-1 - 230/400 V \sim / 6 kA - IEC 60947-2 - 230/400 V \sim
- 10000** - IEC 60898-1 - 127/220 V \sim / 10 kA - IEC 60947-2 - 127/220 V \sim
- Do not accept auxiliaries, and add-on modules
- RCDs: Conform to IEC 61008-1

Pack	Cat.Nos		MCBs	
			Single pole - 230/400 V\sim	
	B curve	C curve	In	Number of modules
10	6049 02	6048 02	6 A	1
10	6049 03	6048 03	10 A	1
10	6049 04	6048 04	13 A	1
10	6049 05	6048 05	16 A	1
10	6049 06	6048 06	20 A	1
10	6049 07	6048 07	25 A	1
10	6049 08	6048 08	32 A	1
10	6049 09	6048 09	40 A	1
10	6049 10	6048 10	50 A	1
10	6049 11	6048 11	63 A	1
			Single pole + neutral - 230 V\sim	
	C curve	In	Number of modules	
5	6048 90 ⁽¹⁾	6 A	2	
5	6048 91 ⁽¹⁾	10 A	2	
5	6048 92 ⁽¹⁾	13 A	2	
5	6048 93 ⁽¹⁾	16 A	2	
5	6047 90 ⁽¹⁾	20 A	2	
5	6047 91 ⁽¹⁾	25 A	2	
5	6047 92 ⁽¹⁾	32 A	2	
	B curve	C curve	In	Number of modules
5	6049 17	6048 17	6 A	2
5	6049 18	6048 18	10 A	2
5	6049 19	6048 19	13 A	2
5	6049 20	6048 20	16 A	2
5	6049 21	6048 21	20 A	2
5	6049 22	6048 22	25 A	2
5	6049 23	6048 23	32 A	2
5	6049 24	6048 24	40 A	2
5	6049 25	6048 25	50 A	2
5	6049 26	6048 26	63 A	2
	B curve	C curve	In	Number of modules
1	6049 32	6048 32	6 A	3
1	6049 33	6048 33	10 A	3
1		6048 34	13 A	3
1	6049 35	6048 35	16 A	3
1	6049 36	6048 36	20 A	3
1	6049 37	6048 37	25 A	3
1	6049 38	6048 38	32 A	3
1	6049 39	6048 39	40 A	3
1	6049 40	6048 40	50 A	3
1	6049 41	6048 41	63 A	3
	C curve	In	Number of modules	
1	6047 96 ⁽¹⁾	6 A	4	
1	6048 94 ⁽¹⁾	10 A	4	
1	6048 95 ⁽¹⁾	13 A	4	
1	6048 96 ⁽¹⁾	16 A	4	
1	6048 97 ⁽¹⁾	20 A	4	
1	6048 98 ⁽¹⁾	25 A	4	
1	6048 99 ⁽¹⁾	32 A	4	
1	6047 97 ⁽¹⁾	40 A	4	
1	6047 98 ⁽¹⁾	50 A	4	
1	6047 99 ⁽¹⁾	63 A	4	

Pack	Cat.Nos		MCBs (continued)	
			4-pole - 400 V\sim	
	C curve	In	Number of modules	
1	6048 47	6 A	4	
1	6048 48	10 A	4	
1	6048 50	16 A	4	
1	6048 51	20 A	4	
1	6048 52	25 A	4	
1	6048 53	32 A	4	
1	6048 54	40 A	4	
1	6048 55	50 A	4	
1	6048 56	63 A	4	

		RCDs			
AC type	A type	Nominal rating (A)	Number of modules		
			2-pole - 230 V\sim - 30 mA		
1	6021 36	25	2		
1	6021 37	40	2		
1	6021 38	63	2		
			2-pole - 230 V\sim - 100 mA		
1	6021 39	25	2		
1	6021 40	40	2		
			2-pole - 230 V\sim - 300 mA		
1	6021 42	25	2		
1	6021 43	40	2		
1	6021 44	63	2		
			4-pole - 400 V\sim - 30 mA		
1	6021 46 ⁽¹⁾	25	4		
1	6021 47 ⁽¹⁾	40	4		
1		63	4		
			4-pole - 400 V\sim - 100 mA		
1	6021 49 ⁽¹⁾	25	4		
1	6021 50 ⁽¹⁾	40	4		
			4-pole - 400 V\sim - 300 mA		
1	6021 52 ⁽¹⁾	25	4		
1	6021 53 ⁽¹⁾	40	4		

(1) Neutral on right-hand side