

MCBs DX-H 10000 - 25 kA


thermal magnetic, high breaking capacity MCBs from 2 A to 125 A
C curve



068 60




068 20



064 76



069 43



070 00

Dimensions (p. 183)
 Technical characteristics (p. 156-158)

Breaking capacity
10000 IEC 60898-1 - 400 V~
25 kA to 12.5 kA - IEC 60947-2 - 400 V~

Pack	Cat.Nos	Single pole - 230/400 V~		
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 230 V/400 V~
1	068 53	2	1	25
1	068 54	3	1	25
1	068 56	6	1	25
1	068 58	10	1	25
1	068 59	13	1	25
1	068 60	16	1	25
1	068 61	20	1	25
1	068 62	25	1	20
1	068 63	32	1	15
1	068 64	40	1	12.5
1	068 65	50	1	12.5
1	068 66	63	1	12.5
1	063 83	80	1.5	12.5
1	063 84	100	1.5	12.5
1	063 85	125	1.5	12.5

Pack	Cat.Nos	3-pole - 400 V~			
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 400 V~ 230 V~	
1	069 33	2	3	25	50
1	069 34	3	3	25	50
1	069 36	6	3	25	50
1	069 38	10	3	25	50
1	069 39	13	3	25	50
1	069 40	16	3	25	50
1	069 41	20	3	25	50
1	069 42	25	3	20	50
1	069 43	32	3	15	50
1	069 44	40	3	15	50
1	069 45	50	3	12.5	25
1	069 46	63	3	12.5	25
1	064 95	80	4.5	12.5	16
1	064 96	100	4.5	12.5	16
1	064 97	125	4.5	12.5	16

Pack	Cat.Nos	Single pole + neutral - 230 V~		
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 230 V~
1	068 96	6	2	25
1	068 98	10	2	25
1	068 99	13	2	25
1	069 00	16	2	25
1	069 01	20	2	25
1	069 02	25	2	20
1	069 03	32	2	15
1	069 04	40	2	15
1	069 05	50	2	12.5
1	069 06	63	2	12.5

Pack	Cat.Nos	3-pole + neutral - 400 V~			
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 400 V~ 230 V~	
1	069 76	6	4	25	50
1	069 78	10	4	25	50
1	069 79	13	4	25	50
1	069 80	16	4	25	50
1	069 81	20	4	25	50
1	069 82	25	4	20	50
1	069 83	32	4	15	50
1	069 84	40	4	15	50
1	069 85	50	4	12.5	25
1	069 86	63	4	12.5	25

Pack	Cat.Nos	2-pole - 230/400 V~			
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 400 V~ 230 V~	
1	069 13	2	2	30	50
1	069 14	3	2	30	50
1	069 16	6	2	30	50
1	069 18	10	2	30	50
1	069 19	13	2	30	50
1	069 20	16	2	30	50
1	069 21	20	2	30	50
1	069 22	25	2	25	50
1	069 23	32	2	20	50
1	069 24	40	2	20	50
1	069 25	50	2	15	25
1	069 26	63	2	15	25
1	064 75	80	3	16	25
1	064 76	100	3	16	25
1	064 77	125	3	16	25

Pack	Cat.Nos	4-pole - 400 V~			
	C curve	Nominal rating (A)	Number of modules	Breaking capacity (kA) IEC 60947-2 400 V~ 230 V~	
1	069 93	2	4	25	50
1	069 94	3	4	25	50
1	069 96	6	4	25	50
1	069 98	10	4	25	50
1	069 99	13	4	25	50
1	070 00	16	4	25	50
1	070 01	20	4	25	50
1	070 02	25	4	20	50
1	070 03	32	4	15	50
1	070 04	40	4	15	50
1	070 05	50	4	12.5	25
1	070 06	63	4	12.5	25
1	065 70	80	6	12.5	16
1	065 71	100	6	12.5	16
1	065 72	125	6	12.5	16

Auxiliaries and accessories (p. 154)

Add-on modules (p. 152)

Supply busbars (p. 249)



B and Z curve, please consult us